

1. Application

EUROFLEX® corner protection profile reduces the potential for injury on existing steps and edges made of concrete, wood and other hard surfaces. It is therefore suitable for covering e.g. stairs, stands, wall crowns and exposed edges.

Environmentally friendly production (double KRAIBURG Relastec GmbH & Co.KG recycling guarantee) and recycling.

2. Material

Rubber granulate: Rubber-Recycling granulate
Binder: MDI Polyurethane

3. Product design

colour: red, green, grey or black
Slight differences in color and fading cannot be avoided.
Surface: open-pore smooth
beveled edges, 2 connectors



4. Dimensions

Length x width x thickness: 1000 x 120 x 90 mm
Side length: 80mm, 50mm
Weight: approx. 5,0 kg
Dimensional tolerances: Length, width: +/- 0.8%, thickness: +/- 2mm

All information without guarantee, subject to change. The Data Sheet is not subject to any change service.
Each current and valid from can be recalled at www.kraiburg-relastec.com/euroflex

page 1 of 2

5. Test Data

The product complies with the requirements of the Equipment Safety Act and has been tested for conformity in accordance with Regulation (EC) 1907/2006 SVHC list and Annex XVII / Production facility inspection

6. Installation

The EUROFLEX® corner protection profiles are to be glued onto the cleaned, dry and smooth surface (we recommend a 1-component PUR adhesive).

The joints of the corner protection profiles must be connected using plug connectors. For further information, please refer to the installation instructions.

All information without guarantee, subject to change. The Data Sheet is not subject to any change service. Each current and valid from can be recalled at www.kraiburg-relastec.com/euroflex

page 1 of 2