

## 1. Application

KOMFORTEX® Floor Protection as a floor covering for boxes, stable alleys, open stables, washing areas and animal enclosures.

Due to its high slip and wear resistance, the product offers optimum protection for the ground and the risk of injuries to the horses.

Available as roll material and easy to install.


## 2. Material

Fine granulated recycled rubber and 15 % of coloured EPDM granulates mixed with polyurethane binder.

## 3. Product Design

colour:

black/blue



black/grey



other colors on request

low colour differences are conditional of material

Surface: fine granulate structure with coloured EPDM granulates

## 4. Dimensions / Tolerances

Width:	1500 mm (+/- 1,5 %)
Thickness:	12 mm (+/- 0,3 mm)
Roll length:	10 00 mm
Volumetric weight:	approx. 1050 kg/m <sup>3</sup>
Basis weight:	approx. 12,6kg/m <sup>2</sup>

All information without guarantee, subject to change. The Data Sheet is not subject to any change service.  
Each current and valid from can be recalled at [www.kraiburg-relastec.com/komfortex](http://www.kraiburg-relastec.com/komfortex)

page 1 of 2

### 5. Product testing

Wear hardness:	approx. 4,0 MPa	(DIN 53577)
Tensile strength:	approx. 1,5 N/mm <sup>2</sup>	(EN ISO 1798)
Elongation at break:	approx. 80 %	(EN ISO 1798)
Abrasion:	max. 200 mm <sup>3</sup>	(DIN 53516)
Hardness:	60 +/- 5 Shore A	(DIN 53505)
Compression set:	approx. 15 %	(DIN 53517)
Coefficient of friction:	μ 0,47 (safe)	(EN 13893: 2002)
Fire resistance:	Efl (B2)	(DIN EN 13501-7)
Light fastness:	2-3	(DIN EN 105-B02:1999-09)
Electrostatic properties:	0,5 kV	(DIN EN 1815:1995-06)
Remaining deformation:	0,21 mm (at 6 mm)	(EN 433:1994-11)
Step sound insulation:	17 dB (at 6 mm)	(DIN EN ISO 140-8:1998-03)
Use with wheel chairs:	for permanent use	(DIN EN 1307:1997-06)
(Tested at 8 mm thickness)		

### Before installation



### After installation



All information without guarantee, subject to change. The Data Sheet is not subject to any change service.  
Each current and valid from can be recalled at [www.kraiburg-relastec.com/komfortex](http://www.kraiburg-relastec.com/komfortex)

page 2 of 2